

SOLIS


26 HP

MORE POWER
MORE SAVINGS



A Product Of

SONALIKA
INTERNATIONAL



STANDARD FEATURES

Engine	Engine Type HP Category No. of Cylinders Aspiration Cubic Capacity (cc) Rated RPM (+/-25mm) Air cleaner Cold Star Max Torque @ RPM (Nm) Exhaust	Mitsubishi S3L2, three Cylinder Engine 26 3 Natural 1318 2700 Dry air cleaner with clogging sensor Yes 75.2@2200 Underhood Downdraft silencer
Transmission	Drive Clutch Gearbox Transmission	4WD Single Clutch 6F+2R Sliding Mesh
Speed (Forward)	Maximum (Speed Km/Hr) Minimum (Speed Km/Hr)	17.05@2700 1.53@2700
Brakes	Brakes Type of actuation Parking Brake	Oil immersed brakes Mechanical Latch Type with Brake Pedals
Differential lock	Differential lock	Yes, Foot Operated
PTO	PTO (rpm) PTO (actuation)	540 @ 2080 ERPM , 540 E @ 1410ERPM, 1000 @ 1514ERPM Mechanical
Steering	Steering	Power
Electrical	Battery Alternator Seven pin trailer socket	12V,50A 12V,40A Yes
Hydraulics	3 point linkage Stay Bars Hydraulic lifting capacity Auxiliary hydraulic circuit Lift rods	Cat 1-N Check Chain 600Kg 1DA Yes
Safety Switch	Clutch Safety Switch	Yes
Capacity (Itrs)(+/-5%) approx.	Fuel tank (Lit)	30
Turning Diameter meter	Turning diameter Without Brakes (m)	6.35
Tyre	Front Rear	6.00-12 8.3-20
Dimension & Weight(+/-5%)	Weight(kg) Wheel Base (mm) Total Length (mm) Total Width (mm) Height (mm) Up to ROPS Min Ground Clearance (mm) min Front Track (mm) Rear Track (mm)	1055 1560 2705 1058 2153 225 894 825
Others	Fuel Indicator gauge Front Toe Hook Front & rear weights with std. Ballast Trailer hitch ROPS	Yes Yes Front weights-15x2 Clevis Hitch/Swinging Drawbar Yes
Optional Features	Tyres	Turf tyres: Front tyre: 23x8.50-12LG 306 12PR TL Rear tyre-33x15.50-16.5 LG 306 10PR TL Industrial tyres: Front tyre-23x8.50-12 SPHD 12PR TL Rear tyre-31x15.50-15 SPHD10 PR TL

Dealer Stamp



International Tractors Limited

H.O: Plot No. 29 and 31, Aggarwal Mall, CBD Ground, Near Karkardooma Court, Delhi-110032 (India). Phone: +91 11 22600700, Fax: +91 11 22377472

Works: Jalandhar Road, Hoshiarpur-146022, Punjab (India). Phone: +91 1882 302220, 302221, Fax: +91 1882 302293, E-mail: exports@sonalika.com, Website: www.sonalika.com.